



## LHC 40

The Leyro Portable dry block temperature calibrator suitable for temperature calibrations, between -35°C ... 165°C  $\pm$ 0,31°F...329°F\* , offers a versatile solution for calibrating thermocouples and RTD's in industrial environments, offering an excellent performance in stability and uniformity, as well as a fast response time. The LHC 40 is easy to use, thanks to its compact and light weight design. Thanks to the large size of the insert, it has a large multi hole capacity and can calibrate a large number of thermocouples at the same time. The diameter of the Dry Block is Ø 60mm and 165 mm of depth



### APPLICATIONS

On-site calibration  
Maintenance and Service  
All kind of Industrys  
Machinery Construction

### HIGHLIGHTS

Fast , Compact and Light  
High Calibration Capacity  
Insert Ø 60mm Length 165mm  
Different types of inserts  
Temperature Range: -35°C...165°C\*  
-31°F...329°F\*  
Stability:  $\pm$  0,03°C  
Warranty: 3 Years



#### General Information

Easy and intuitive temperature controller with 4 digits and a resolution of 0,1  
Integrated PT 100 probe for reference temperature measurements  
Accuracy:  $\pm$ 0,3°C / $\pm$  32,54°F  
Temperature Stability:  $\pm$ 0,03°C  
Uniformity :  $\pm$  0,05°C



## Technical Data

### Large Capacity Block

Operating Temperature Range(°C)	-35...165°C* / -31...329°F*
Accuracy	± 0,3°C
Stability:	± 0,03°C
Resolution	± 0.1°C
Uniformity	± 0,05°C
Temperature Control	Internal PT100
Calibration Volume	Ø 60mm x 165 mm
Heating Time	From -5 to 100°C: 25 Minutos
Cooling Time	From 25 to -25°C 45 Minutos
Housing and assembly	Portable
Dimensions An x La x Al (cm)	280 x 280 x 400
Weight (kg)	11 kg approx.
Supply	100 ... 234 Vac 50/60 Hz
Power Consumption	Approx 310 W
Standar insert	1 x Ø 3,5 /1 x Ø 6,5/ 1 x Ø 8,5/ 1 x Ø 10,5
Optional Inserts	2 x Ø 3,5 /2x Ø 4,5/ 2 x Ø 6,5/ 2 x Ø 8,5/ 2 x Ø 10,5 3 x Ø 3,5 /3x Ø 6,5/ 3 x Ø 8,5/3 x Ø 10,5 2 x Ø 3,5 /2x Ø 4,5/2 x Ø 5,5/2 x Ø 6,5/ 1 x Ø 8,5 /2 x Ø 9,5/1 x Ø 10,5

\*Minimum Temperature Range is 55 ° C / 131°F, below ambient. Absolute minimum -35°C / -31°F

## Scope of delivery

Basic Instrument LHC 40

Power Cord

Standar Insert: A 1 x Ø 3,5 /1 x Ø 6,5/ 1 x Ø 8,5/ 1 x Ø 10,5

Manufacturing Traceable Calibration Certificate 5 Points

Instruction Manual

3 Years Warranty against factory defects

## Optional

Trolley transport case with wheels and handle.


ISO 17025 Calibration Certificate (ENAC).

Optional Inserts: B: 2 x Ø 3,5 /2x Ø 4,5/ 2 x Ø 6,5/ 2 x Ø 8,5/ 2 x Ø 10,5

C: 3 x Ø 3,5 /3x Ø 6,5/ 3 x Ø 8,5/3 x Ø 10,5

D :2 x Ø 3,5 /2x Ø 4,5/2 x Ø 5,5/2 x Ø 6,5/ 1 x Ø 8,5 /2 x Ø 9,5/1 x Ø 10,5


E: Blank (without holes).




A




B



C



D



E



**thermo-electra**  
temperature sensor solutions

Thermo Electra B.V.  
Weteringweg 10  
2641KM Pijnacker  
The Netherlands

Phone +31 (0)15 - 3621200  
Fax +31 (0)15 - 3694082  
Email sales@thermo-electra.com  
http://www.thermo-electra.com

