1088 Exd and Extb SS316 connectionhead

Product information	
	ATEX and IECEx approved stainless steel 316 connectionhead with screw-lid and stainless steel chain
ATEX	ATEX II 2GD
	Ex db IIC Gb Ta = -40°C to 85°C
	Ex tb IIIC Db IP68
IECEx	Ex db IIC Gb Ta = -40°C to 85°C
	Ex tb IIIC Db IP68
Technical information	
Material	Stainless steel 316
Temperature rating	-40°C up to +85°C
Ingress protection	IP66 NEMA 4X
Cable entry	1/2"NPT, 3/4"NPT, 1/2"BSP or M20x1.5
Proces connection	1/2"NPT, 3/4"NPT, 1/2"BSP or M20x1.5
Ceramic connection blocks	33 and 40mm
Weight	1.2kg (2.7lbs)
Surface treatment	Electro polished

Ordering code

*This datasheet is purely indicative, build-up of model code may vary from this datasheet.

Model	1088

thermo-electra
temperature sensor solutions

Thermo Electra B.V.
Weteringweg 10
2641KM Pijnacker
The Netherlands

Phone +31 (0)15 - 3621200
Fax +31 (0)15 - 3694082
Email sales@thermo.nl
http://www.thermo-electra.com