

# TE1028 Multiple thermocouple circuit panel horizontal

## Application

<b>Female multi panel</b>	Thermocouple and RTD circuits
<b>Contacts</b>	Springloaded thermocouple contacts
<b>Materials</b>	Glass filled thermocouple body with original thermocouple material contacts
<b>Front</b>	Aluminium anodized for full corrosion protection

## Temperature rating

<b>Temperature limit</b>	Maximum 200°C
--------------------------	---------------

## Construction

<b>Body</b>	Glass filled thermoplastic material
<b>Design</b>	Stainless steel bracket mounted with 2 screws
<b>Molded barriers</b>	Prevent short circuit
<b>Identified</b>	Scratchproof numbering

## Wire size

<b>Accepts wires</b>	From 0.2 mm to 2.0 mm
<b>Colour code</b>	According thermocouple



## Dimensions in mm

Circuits	Rows	L	H
1	1	38	38
6	1	146	67
12	1	260	67
24	2	260	115

## Ordering code

\*This datasheet is purely indicative, build-up of model code may vary from this datasheet.

Model	TE 1028				
No. of circuits per row					
No. of rows					
Calibration					
Colour code IEC or ANSI					

H9-2 Rev. 0 07/07



**thermo-electra**  
temperature sensor solutions

Thermo Electra B.V.  
Weteringweg 10  
2641KM Pijnacker  
The Netherlands

Phone +31 (0)15 - 3621200  
Fax +31 (0)15 - 3694082  
Email sales@thermo.nl  
<http://www.thermo-electra.com>

