

# Type A connectionhead

## Product information

General purpose aluminium connectionhead with removeable lid

## Technical information

<b>Material body</b>	Aluminium pressure die-casting
<b>Material cover</b>	Aluminium press sheet
<b>Material cable gland</b>	Nickelplated brass
<b>Temperature rating</b>	-40°C up to +100°C - oil-proof rubber -40°C up to +150°C - silicone rubber
<b>Cable entry</b>	M20x1.5, 1/2"BSP (G1/2") or 1/2"NPT
<b>Proces connection</b>	13, 15.3, 15.5, 15.8, 22.3, 22.5, 22.8, 24.8, 26.8, 28.8 or 32.5mm bore M12, M18, M20, M24 or M32 1/2"BSP (G1/2"), 3/4"BSP (G3/4"), 1/2"NPT or 3/4"NPT
<b>Mounting space</b>	ø56x25mm
<b>Surface treatment</b>	Polyester, Epoxy or Creodur coating Available in many colours upon request



## Ordering code

\*This datasheet is purely indicative, build-up of model code may vary from this datasheet.

Model

A

H9-4 Rev.0 7/07



**thermo-electra**  
temperature sensor solutions

Thermo Electra B.V.  
Weteringweg 10  
2641KM Pijnacker  
The Netherlands

Phone +31 (0)15 - 3621200  
Fax +31 (0)15 - 3694082  
Email sales@thermo.nl  
<http://www.thermo-electra.com>

