

# Type DANW connectionhead with window

## Product information

General purpose aluminium connectionhead with window and swing cover. Useable for lcd displays

## Technical information

|                             |  |
|-----------------------------|--|
| <b>Material body</b>        | Aluminium pressure die-casting   |
| <b>Material cover</b>       | Aluminium pressure die-casting   |
| <b>Material window</b>      | Polycarbonate, restricted resistance to organic solvent  |
| <b>Material cable gland</b> | Nickelplated brass   |
| <b>Temperature rating</b>   | -40÷80°C - oil-proof rubber  |
| <b>Cable entry</b>          | M20x1.5, 1/2"BSP (G1/2") or 1/2"NPT  |
| <b>Proces connection</b>    | 15.3, 22.5, 26.5 or 32.5mm bore<br>M24x1.5, 3/8"BSP (G3/8"), 1/2"BSP (G1/2"), 1/2"NPT or 3/4"NPT |
| <b>Surface treatment</b>    | Polyester, Epoxy or Creodur<br>Available in many colours upon request                            |
| <b>Option</b>               | Snap-lock  |



## Ordering code

\*This datasheet is purely indicative, build-up of model code may vary from this datasheet.

Model

DANW

H9-4 Rev.0 7/07



**thermo-electra**  
temperature sensor solutions

Thermo Electra B.V.  
Weteringweg 10  
2641KM Pijnacker  
The Netherlands

Phone +31 (0)15 - 3621200  
Fax +31 (0)15 - 3694082  
Email [sales@thermo.nl](mailto:sales@thermo.nl)  
<http://www.thermo-electra.com>

