

Type DANA swing cover connectionhead

Product information

General purpose aluminium connectionhead with swing cover

Technical information

Material body	Aluminium pressure die-casting
Material cover	Aluminium pressure die-casting
Material cable gland	Nickelplated brass
Temperature rating	-40°C up to +100°C - oil-proof rubber -40°C up to +150°C - silicone rubber
Cable entry	M20x1.5, 1/2"BSP (G1/2") or 1/2"NPT
Proces connection	15.3, 22.5, 26.5 or 32.5mm bore M24x1.5, 1/2"BSP (G1/2"), 3/8"BSP (G3/8"), 1/2"NPT or 3/4"NPT
Mounting space	Ø56x13mm, Ø42x40mm
Surface treatment	Polyester, Epoxy or Creodur Available in many colours upon request
Option	Snap-lock



Ordering code

*This datasheet is purely indicative, build-up of model code may vary from this datasheet.

Model

DANA

H9-4 Rev.0 7/07



thermo-electra
temperature sensor solutions

Thermo Electra B.V.
Weteringweg 10
2641KM Pijnacker
The Netherlands

Phone +31 (0)15 - 3621200
Fax +31 (0)15 - 3694082
Email sales@thermo.nl
<http://www.thermo-electra.com>

