

Type DANWH window connectionhead

Product information

General purpose aluminium connectionhead with swing cover and window for LCD display.

Technical information

Material body	Aluminium pressure die-casting
Material cover	Aluminium pressure die-casting
Material window	Polycarbonate, restricted resistance to organic solvent
material cable gland	Nickelplated brass
Temperature rating	-40°C up to 80°C - oil-proof rubber
Cable entry	M20x1.5, 1/2"BSP (G1/2") or 1/2"NPT
Proces connection	15.3, 22.5, 26.5 or 32.5mm bore M24x1.5, 1/2"BSP (G1/2"), 3/8"BSP (G3/8"), 1/2"NPT or 3/4"NPT
Ingress protection	IP68
Mounting space	Ø45x16mm, Ø45x35mm
Surface treatment	Polyester, Epoxy or Creodur coating Available in many colours upon request
Option	Snap-lock



Ordering code

*This datasheet is purely indicative, build-up of model code may vary from this datasheet.

Model

DANWH

H9-4 Rev.0 7/07



thermo-electra
temperature sensor solutions

Thermo Electra B.V.
Weteringweg 10
2641KM Pijnacker
The Netherlands

Phone +31 (0)15 - 3621200
Fax +31 (0)15 - 3694082
Email sales@thermo.nl
<http://www.thermo-electra.com>

