

Type DANHex ATEX Exe and Extb connectionhead

Product information

	ATEX Exe and Extb approved die-cast aluminium connectionhead with high swing cover
ATEX	II 2G Ex eb IIC Gb II 2D Ex tb IIIC Db
ATEX certificate	FTZU 03 ATEX 0073U

Technical information

Material body	Aluminium pressure die-casting
Material cover	Aluminium pressure die-casting
Temperature rating	Service temperature: T _{serv} = -40°C up to +100°C
Cable entry	M20x1.5 or 1/2"NPT
Proces connection	M20x1.5 or M24x1.5 1/2"BSP (G1/2"), 3/8"BSP (G3/8"), 3/4"BSP (G3/4"), 1/2"NPT or 3/4"NPT
Ingress protection	IP68
Mounting space	Ø45x16mm, Ø60x40mm
Surface treatment	Polyester, Epoxy or Creodur Available in many colours upon request
Note	Will be supplied without cable gland!



Ordering code

*This datasheet is purely indicative, build-up of model code may vary from this datasheet.

Model

DANHex

H9-4 Rev.0 7/07



thermo-electra
temperature sensor solutions

Thermo Electra B.V.
Weteringweg 10
2641KM Pijnacker
The Netherlands

Phone +31 (0)15 - 3621200
Fax +31 (0)15 - 3694082
Email sales@thermo.nl
<http://www.thermo-electra.com>

