

# Exd Connectionhead with window

## Product information

	ATEX and IECEx Exd approved die-cast aluminium connectionhead with screw-cover and window
<b>ATEX</b>	II 2 G Ex db II C Gb II 2D Ex tb IIIC Db
<b>ATEX certificate</b>	FTZU 03 ATEX 0074U
<b>IECEx</b>	Ex db II C Gb Ex tb IIIC Db
<b>IECEx certificate</b>	IECEx FTZU 14.0003U

## Technical information

<b>Material body</b>	Aluminium pressure die-casting, max 0.5%Mg
<b>Material cover</b>	Aluminium pressure die-casting, max 0.5%Mg
<b>All other metal parts</b>	Stainless steel
<b>Temperature rating</b>	Tserv= -50°C up to +85°C - silicone rubber Tserv= -20°C up to +85°C - fluoroelastomer rubber
<b>Cable entry</b>	M20x1.5, 1/2"NPT or 3/4"NPT BSP (G") threads are possible but without certification!
<b>Proces connection</b>	M20x1.5, M24x1.5 or M27x2 1/2"NPT or 3/4"NPT BSP (G") threads possible with certificate but flamepath must be determind. Please contact our sales team for information
<b>Ingress protection</b>	IP68
<b>Mounting space</b>	Ø52x30mm
<b>Surface treatment</b>	Polyester, Epoxy or Creodur Available in many colours upon request



## Ordering code

\*This datasheet is purely indicative, build-up of model code may vary from this datasheet.

Model

XDADW

H9-4 Rev.0 7/07



**thermo-electra**  
temperature sensor solutions

Thermo Electra B.V.  
Weteringweg 10  
2641KM Pijnacker  
The Netherlands

Phone +31 (0)15 - 3621200  
Fax +31 (0)15 - 3694082  
Email [sales@thermo.nl](mailto:sales@thermo.nl)  
<http://www.thermo-electra.com>

