

DWK 6110 Vibration proof thermocouple

Protection tube	
Construction	Closed-end tube
Material	SS 316 - (Wst 1.4401) standard, other materials possible
Diameter	9.0mm standard, other diameters possible
Insertion length	100mm standard, other lengths possible
Process connection	M20x1.5, 1/2"BSP (G1/2"), 1/2"NPT or other threads possible
Extension length	100mm standard, other lengths possible
Connection head	
Material	Aluminium, plastic or stainless steel
Cable entry	M20x1.5 cable gland standard, other threads possible
Measuring insert	
Construction	Springloaded and replaceable
Diameter	6.0mm
Length	E = L + 35 mm
Material	SS 316 - (Wst 1.4401) standard, other materials possible
Insulation	Mineral insulated MgO
Thermocouple	
Calibration	K, T, J, E, N, U or L
For duplex	KK, TT, JJ, EE, NN, UU or LL
Accuracy	According IEC 60584 / DIN 43710
Options	
Transmitter 4-20mA	In-Head transmitter, standard or Ex version. Please select from our standard range or specify your own standard
Swing-Cover head	DAN, transmitter direct mounted on measuring insert
High Swing-Cover head	DAN-H, transmitter in cover, insert with ceramic block



Ordering code

*This datasheet is purely indicative, build-up of model code may vary from this datasheet.



thermo-electra
temperature sensor solutions

Thermo Electra B.V.
Weteringweg 10
2641KM Pijnacker
The Netherlands

Phone +31 (0)15 - 3621200
Fax +31 (0)15 - 3694082
Email sales@thermo.nl
http://www.thermo-electra.com