

## Applications

Multi spot thermometer for bulk stored liquids, Food, Crude oil, Bitumen, Chemicals, Refined liquids

## Protection tube

### Construction

Flexible convoluted gas-tight tube

### Material

Stainless steel 316 standard, other materials possible

### Design

Gas and liquid tight. Screwed adjustable flange connection max. 2bar @100°C. Otherwise fixed welded to flange.

### Tube diameter

19mm standard, other diameters possible

### Process connection

M25 or 1/2"BSPP standard, other threads possible

### Temperature range

-20 / +200°C

## Connection cable

### Cable

3000mm weatherproof IP65 sealed cable standard, other lengths possible

## Elements

### Type

Wirewound precision Pt100 detectors

Vibration proof superior class

### Accuracy

According to IEC 60751 Cl. B, A or AA

## Options


Junctionbox aluminium or stainless steel also possible in Ex version

Temperature transmitters, standard or Ex version. Please specify brand.

3Kg Anchor weight, Flange connection, other temperature limits and Ex version

## Datasheet notification

**This datasheet is purely indicative, build-up of model code may vary from this datasheet**



## Ordering code

\*This datasheet is purely indicative, build-up of model code may vary from this datasheet.

Model

ML7090		
--------	--	--

Number of sensors

L1 to Ln to specify



**thermo-electra**  
temperature sensor solutions

Thermo Electra B.V.  
Weteringweg 10  
2641KM Pijnacker  
The Netherlands

Phone +31 (0)15 - 3621200  
Fax +31 (0)15 - 3694082  
Email sales@thermo.nl  
http://www.thermo-electra.com

