

DWR 6000 Threaded Pt100 sensor with valve connector

Protectiontube

Construction	Welded protectiontube, liquid and gas tight
Material	SS 316 - (Wst 1.4401) standard, other materials possible
Insertion length	50mm to 400mm
Diameter	6.0mm standard, other diameters possible
Process connection	1/2"BSP (G1/2") standard, other threads possible
Maximum process pressure	Suitable up to 40 Bar

Connector

Valve connector	Connector according to DIN EN 175-803 (Hirschmann GSP or equivalent (max. 120°C at the connector)
Ingress protection	IP65

Sensor

Type	Single Pt100
Measuring range	-30 / +180°C
Measuring current	1mA
Accuracy	According IEC 60751 Class B standard, other classes possible
Connection	2 wires

Testing

Insulation test	Performed with 250Vdc @ 20°C
Insulation minimum	>100 MOhm

Options

Sensor connection	3 or 4-wire system
Extended measuring range	-50 / +260°C
High temperature versions	-30 / 600 °C



Ordering code

*This datasheet is purely indicative, build-up of model code may vary from this datasheet.

Model	DWR 6000			
Length "L" in mm.		↑	↑	↑
Diameter "D" in mm			↑	↑
Process connection				↑



thermo-electra
temperature sensor solutions

Thermo Electra B.V.
Weteringweg 10
2641KM Pijnacker
The Netherlands

Phone +31 (0)15 - 3621200
Fax +31 (0)15 - 3694082
Email sales@thermo.nl
<http://www.thermo-electra.com>

